

**2000 SUPER DUTY F-SERIES TRUCKS  
PAYLOAD PACKAGE SELECTOR CHARTS**

**F-250 Pickup**

Series	Model	Wheel Base (inches)	Pkg#	Opt. Code	49 States				California Emissions Powertrains			
					Gasoline		Diesel*		Gasoline		Diesel*	
					Max. Payload (lbs)	GVWR (lbs)	Max. Payload (lbs)	GVWR (lbs)	Max. Payload (lbs)	GVWR (lbs)	Max. Payload (lbs)	GVWR (lbs)
4x2	Regular Cab	137	1	201	3722	8800	3215	8800	3840	8800	3215	8800
	Super Cab	142	1	201	3661	8800	2985	8800	3610	8800	2985	8800
		158	1	201	3443	8800	2880	8800	3520	8800	2880	8800
	Crew Cab	156	1	201	3313	8800	2675	8800	3310	8800	2675	8800
		172	1	201	3144	8800	2580	8800	3220	8800	2580	8800
4x4	Regular Cab	137	1	201	3285	8800	2720	8800	3360	8800	2720	8800
	SuperCab	142	1	201	3223	8800	2535	8800	3165	8800	2535	8800
		158	1	201	2992	8800	2440	8800	3075	8800	2440	8800
	Crew Cab	156	1	201	2869	8800	2240	8800	2865	8800	2240	8800
		172	1	201	2733	8800	2145	8800	2775	8800	2145	8800

\* Note: Diesel Max Payload numbers reflect use of an automatic transmission

**2000 SUPER DUTY F-SERIES TRUCKS  
PAYLOAD PACKAGE SELECTOR CHARTS**

**F-350 Pickup**

Series	Model	Wheel Base (inches)	Pkg#	Opt. Code	49 States				California Emissions Powertrains			
					Gasoline		Diesel*		Gasoline		Diesel*	
					Max. Payload (lbs)	GVWR (lbs)	Max. Payload (lbs)	GVWR (lbs)	Max. Payload (lbs)	GVWR (lbs)	Max. Payload (lbs)	GVWR (lbs)
4X2	Regular Cab	137 SRW	1	203	4796	9900	4305	9900	4640	9700	4100	9700
		137 DRW	1	205	5859	11200	5290	11200	5525	11000	5085	11000
	SuperCab	142 SRW	1	203	4735	9900	4075	9900	4390	9700	3865	9700
		158 SRW	1	203	4517	9900	3970	9900	4305	9700	3760	9700
		158 DRW	1	205	5592	11200	4955	11200	5190	11000	4750	11000
	Crew Cab	156 SRW	1	203	4387	9900	3765	9900	4095	9700	3555	9700
		156 DRW	1	205	5448	11200	4750	11200	4980	11000	4545	11000
		172 SRW	1	203	4218	9900	3670	9900	4005	9700	3460	9700
		172 DRW	1	205	5289	11200	4655	11200	4890	11000	4450	11000
4x4	Regular Cab	137 SRW	1	203	4390	9900	3810	9900	4150	9700	3605	9700
		137 DRW	1	205	5375	11200	4800	11200	5030	11000	4590	11000
	SuperCab	142 SRW	1	203	4328	9900	3625	9900	3950	9700	3415	9700
		158 SRW	1	203	4097	9900	3530	9900	3865	9700	3355	9700
		158 DRW	1	205	5164	11200	4605	11200	4840	11000	4400	11000
	Crew Cab	156 SRW	1	203	3974	9900	3330	9900	3660	9700	3125	9700
		156 DRW	1	205	5035	11200	4315	11200	4550	11000	4110	11000
		172 SRW	1	203	3838	9900	3235	9900	3570	9700	3030	9700
		172 DRW	1	205	4775	11200	4225	11200	4455	11000	4015	11000

\* Note: Diesel Max. Payload numbers reflect use of an automatic transmission

**2000 SUPER DUTY F-SERIES TRUCKS  
PAYLOAD PACKAGE SELECTOR CHARTS**

**F-350 Chassis Cab**

Series	Model	Wheel Base (inches)	Pkg#	Opt. Code	49 States				California Emissions Powertrains			
					Gasoline		Diesel*		Gasoline		Diesel*	
					Max. Payload (lbs)	GVWR (lbs)	Max. Payload (lbs)	GVWR (lbs)	Max. Payload (lbs)	GVWR (lbs)	Max. Payload (lbs)	GVWR (lbs)
4x2	Regular Cab	141 SRW	1	203	5065	9900	4505	9900	4745	9700	4295	9700
		141 DRW	1	205	6053	11200	6820	12500	5730	11000	6820	12500
		165 DRW	1	205	5954	11200	6715	12500	5655	11000	6715	12500
	SuperCab	162 SRW	1	203	4775	9900	4165	9900	4115	9700	3955	9700
		162 DRW	1	205	5754	11200	6450	12500	5400	11000	6450	9700
		Crew Cab	176 SRW	1	203	4512	9900	3850	9900	4115	9700	3660
176 DRW	1		205	5507	11200	6155	12500	5085	11000	6155	12500	
4x4	Regular Cab	141 SRW	1	203	4620	9900	4040	9900	4285	9700	3835	9700
		141 DRW	1	205	5566	11200	6330	12500	5270	11000	6330	12500
		165 DRW	1	205	5468	11200	6250	12500	5195	11000	6250	12500
	SuperCab	162 SRW	1	203	4330	9900	3730	9900	3975	9700	3520	9700
		162 DRW	1	205	5332	11200	6015	12500	4965	11000	6015	12500
	Crew Cab	176 SRW	1	203	4053	9900	3435	9900	3680	9700	3225	9700
176 DRW		1	205	5036	11200	5720	12500	4670	11000	5720	12500	

\* Note: Diesel Max. Payload numbers reflect use of an automatic transmission.

**2000 SUPER DUTY F-SERIES TRUCKS  
PAYLOAD PACKAGE SELECTOR CHARTS**

**F-450 Chassis Cab**

Series	Model	Wheel Base (inches)	Pkg#	Opt. Code	49 States				California Emissions Powertrains			
					Gasoline		Diesel*		Gasoline		Diesel*	
					Max. Payload (lbs)	GVWR (lbs)	Max. Payload (lbs)	GVWR (lbs)	Max. Payload (lbs)	GVWR (lbs)	Max. Payload (lbs)	GVWR (lbs)
4X2	Regular Cab	141 DRW	1	207	8928	15000	8525	15000	9030	15000	8525	15000
		165 DRW	1	207	8826	15000	8465	15000	8975	15000	8465	15000
		201 DRW	1	207	8516	15000	8150	15000	8640	15000	8150	15000
	Crew Cab	176 DRW	1	207	8362	15000	7900	15000	8415	15000	7900	15000
4X4	Regular Cab	141 DRW	1	207	8608	15000	8200	15000	8700	15000	8200	15000
		165 DRW	1	207	8500	15000	8145	15000	8645	15000	8145	15000
		201 DRW	1	207	8164	15000	7815	15000	8310	15000	7815	15000
	Crew Cab	176 DRW	1	207	8030	15000	7580	15000	8085	15000	7580	15000

\* Note: Diesel Max. Payload numbers reflect use of an automatic transmission.

**2000 SUPER DUTY F-SERIES TRUCKS  
PAYLOAD PACKAGE SELECTOR CHARTS**

**F-550 Chassis Cab**

Series	Model	Wheel Base (inches)	Pkg#	Opt. Code	49 States				California Emissions Powertrains			
					Gasoline		Diesel*		Gasoline		Diesel*	
					Max. Payload (lbs)	GVWR (lbs)	Max. Payload (lbs)	GVWR (lbs)	Max. Payload (lbs)	GVWR (lbs)	Max. Payload (lbs)	GVWR (lbs)
4x2	Regular Cab	141 DRW	1	208	11296	17500	10970	17500	11425	17500	10970	17500
		165 DRW	1	208	11193	17500	10920	17500	11375	17500	10920	17500
		201 DRW	1	208	10896	17500	10585	17500	11035	17500	10585	17500
	201 DRW	2	209	12284	19000	11970	19000	12425	19000	11970	19000	
	Crew Cab	176 DRW	1	208	10716	17500	10350	17500	10815	17500	10350	17500
4x4	Regular Cab	141 DRW	1	208	10960	17500	10640	17500	11095	17500	10640	17500
		165 DRW	1	208	10846	17500	10590	17500	11040	17500	10590	17500
		201 DRW	1	208	10543	17500	10260	17500	10705	17500	10260	17500
	Crew Cab	176 DRW	1	208	10379	17500	10020	17500	10485	17500	10020	17500

\* Note: Diesel Max. Payload numbers reflect use of an automatic transmission.

Order Guide Supplemental Reference

**2000 SUPER DUTY F-SERIES TRUCKS  
SNOW PLOW APPLICATION CHARTS**

**4x4 Pickup \***

Cab Style	Wheelbase	Engine	F-250	F-350
Regular Cab	137"	5.4L V-8	100/750	100/750
		6.8L V-10	100/750	100/750
		7.3L V-8 Diesel	100/680	100/680
SuperCab	142"	5.4L V-8	100/750	100/750
		6.8LV-10	100/750	100/750
		7.3L V-8 Diesel	N/R	N/R
	158"	5.4L V-8	100/750	100/750
		6.8LV-10	100/750	100/750
		7.3L V-8 Diesel	N/R	N/R
Crew Cab	156"	5.4LV-8	100/750	100/750
		6.8LV-10	100/750	100/750
		7.3L V-8 Diesel	N/R	N/R
	172"	5.4LV-8	100/750	100/750
		6.8L V-8	100/750	100/750
		7.3L V-8 Diesel	N/R	N/R

\* Includes Pickups ordered with the Pickup Box Delete option (66D).

**Legend:**

100 / 750 = Maximum 100 lbs. of permanently-attached hardware / Maximum 750 lbs. of removable plow blade and hardware (maximum plow system weight is the sum of these). The plow and hardware weight limits shown are based upon a vehicle with maximum buildable option content.

N/R = Not recommended for snow plow application. Snow Plow Package (86M) not available.

**4x4 Chassis Cab**

Cab Style	Wheelbase	Engine	F-350	F-450	F-550
Regular Cab	141"	5.4L V-8	100/750	X	X
		6.8LV-10	100/750	125/900	125/900
		7.3L V-8 Diesel	100/750	125/900	125/900
	165"	5.4L V-8	100/750	X	X
		6.8L V-10	100/750	125/900	125/900
		7.3L V-8 Diesel	100/750	125/900	125/900
	201"	5.4L V-8	X	X	X
		6.8LV-10	X	125/900	125/900
		7.3L V-8 Diesel	X	100/750	100/750
Super Cab	162"	5.4L V-8	100/750	X	X
		6.8L V-10	100/750	X	X
		7.3L V-8 Diesel	100/680	X	X
Crew Cab	176"	5.4L V-8	100/750	X	X
		6.8LV-10	100/750	125/900	125/900
		7.3L V-8 Diesel	N/R	125/900	125/900

**Legend:**

100 / 750 = Maximum 100 lbs. of permanently-attached hardware / Maximum 750 lbs. of removable plow blade and hardware (maximum plow system weight is the sum of these). The plow and hardware weight limits shown are based upon a vehicle with maximum buildable option content.

N/R= Not recommended for snow plow application. Snow Plow Package (86M) not available.

X = Unavailable vehicle configuration

Order Guide Supplemental Reference

**2000 SUPER DUTY F-SERIES TRUCKS  
CAB-TO-AXLE DIMENSION CHART**

<b>Model</b>	<b>Cab</b>	<b>Wheelbase (inches)</b>	<b>Cab-to-Axle (CA) (inches)</b>	<b>Pickup</b>	<b>Box Delete <sup>(1)</sup></b>	<b>Chassis Cab</b>
<b>F-250</b>	Reg. Cab	137	56	8' Box	Yes	--
	Super Cab	142	40	6.75' Box	--	--
	Super Cab	158	56	8' Box	Yes	--
	Crew Cab	156	40	6.75' Box	--	--
	Crew Cab	172	56	8' Box	Yes	--
<b>F-350</b>	Reg. Cab	137	56	8' Box	Yes <sup>(2)</sup>	--
	Reg. Cab	141	60	--	--	Yes
	Reg. Cab	165	84	--	--	Yes
	Super Cab	142	40	6.75' Box	--	--
	Super Cab	158	56	8' Box	Yes <sup>(2)</sup>	--
	Super Cab	162	60	--	--	Yes
	Crew Cab	156	40	6.75' Box	--	--
	Crew Cab	172	56	8' Box	Yes <sup>(2)</sup>	--
Crew Cab	176	60	--	--	Yes	
<b>F-450</b>	Reg. Cab	141	60	--	--	Yes
	Reg. Cab	165	84	--	--	Yes
	Reg. Cab	201	120	--	--	Yes
	Crew Cab	176	60	--	--	Yes
<b>F-550</b>	Reg. Cab	141	60	--	--	Yes
	Reg. Cab	165	84	--	--	Yes
	Reg. Cab	201	120	--	--	Yes
	Crew Cab	176	60	--	--	Yes

(1) Box Delete available on 8' box only

(2) DRW only

Order Guide Supplemental Reference

**2000 SUPER DUTY F-SERIES TRUCKS  
Pickup Ride Height Chart**

The 2000 Super Duty's tough monobeam 4x4 front axle and spring capacity result in a durable vehicle with ride heights which need to be considered when towing with a fifth wheel or gooseneck trailer.

For the Super Duty F-250 and 350 4x4\*, the following chart provides the maximum ride heights.

<b>Model</b>	<b>Maximum Ride Height** (inches)</b>
F-250	56-57
F-350 SRW	58-59
F-350 DRW	57-58

\* Vehicles with other configurations may have varying ride heights

\*\* Maximum Ride Height refers to the maximum height of the tailgate

Please refer to the [RV and Trailer Towing Guide](#) for more trailer towing information.

<b>2000 SUPER DUTY F-SERIES TRUCKS</b> <b>Max Front GAWR Application Chart</b>
---

The Max Front GAWR package insures customers that the vehicle they have purchased has the maximum possible front GAWR for the given vehicle configuration. It contains the same equipment as the Heavy Duty Suspension package, except that the "one up" front springs have been replaced with heavier springs in order to attain Max Front GAWR. *Customers should be aware that choosing the Max Front GAWR package may result in a deterioration of ride quality.*

Below are the restrictions for the Max Front GAWR package on F-250 and F-350:

Model	Drive Type	Availability
F-250	4x2	Available for body companies and qualified fleet customers, requires Modified Vehicle Engineering (MVE) approval*
	4x4	Available for all customers
F-350	4x2	Available for body companies and qualified fleet customers, requires Modified Vehicle Engineering (MVE) approval*
	4x4	Available for all customers

\* This restriction is due to the potential increase in tire wear associated with applying the Max Front GAWR package to vehicles with twin I-beam suspension. Please fax (313) 337-2754 to obtain the necessary approval.

Below are the restrictions for the Max Front GAWR package on F-450 and F-550:

Model	Engine	Availability
F-450	Diesel	N/A (F-450s with diesel engines already have the maximum front GAWR springs)
	Gasoline	Available for all customers
F-550	Diesel	N/A (F-550s with diesel engines already have the maximum front GAWR springs)
	Gasoline	Available for all customers

Please refer to the Body Builder's Guide for further information regarding front GAWR.