

2015 FORD F-SERIES SUPER DUTY TECHNICAL SPECIFICATIONS

POWERTRAIN/CHASSIS		
POWERTRAIN	6.2L 2V V8	6.7L 4V V8
Engine type	SOHC gas (flex fuel)	OHV Power Stroke® Turbo-Diesel
Block/head	Cast iron/aluminum	Compacted graphite iron/aluminum
Bore x stroke	4.02 x 3.74 in.	3.90 x 4.25 in.
Displacement	379 cu. in., 6,210 cc	406 cu. in., 6,651 cc
Compression ratio	9.8:1	16.2:1
Fuel injection	Sequential electronic	High-pressure common rail
Valve operation	Roller-rocker shaft	Pushrod/rocker arms
Horsepower	385 @ 5,500 rpm (1); 316 @ 4,179 rpm (2)	440 @ 2,800 rpm
Torque	405 lb.-ft. @ 4,500 rpm (1); 397 lb.-ft. @ 4,179 rpm (2)	860 lb.-ft. @ 1,600 rpm
Oil capacity	Seven quarts	13 quarts
Coolant capacity	21.0 quarts	38.85 quarts (27.8 quarts main cooling system plus 11.05 quarts secondary cooling system)
Fuel capacity	35 gallons	26 gallons (137-in., 142-in. and 156-in. WB), 37.5 gallons (158-in. and 172-in. WB)
Recommended fuel	Regular unleaded or E85	Ultra-low sulfur diesel or B20 (containing 20 percent or less biodiesel)
Transmission	TorqShift® heavy-duty six-speed automatic with SelectShift®	TorqShift heavy-duty six-speed automatic with SelectShift
Gear ratios		
1st	3.97:1	3.97:1
2nd	2.31:1	2.31:1
3rd	1.51:1	1.51:1
4th	1.14:1	1.14:1
5th	0.85:1	0.85:1
6th	0.67:1	0.67:1
Reverse	3.12:1	3.12:1
Available axle ratios	3.73, 4.30	3.31, 3.55, 3.73, 4.30
(1) Under 10,000 lbs. (GVWR). (2) Over 10,000 lbs. (GVWR)		

2015 FORD F-SERIES SUPER DUTY TECHNICAL SPECIFICATIONS

SUSPENSION	
Front	
4x2	Independent twin I-beam (narrow front track) with coil springs, shock absorbers, stabilizer bar (F-250/F-350)
4x4	Mono beam (narrow front track) with coil springs, shock absorbers, stabilizer bar (F-250/F-350) Mono beam (wide front track) with coil springs, shock absorbers, stabilizer bar (F-450/F-350 DRW with Trailer Tow Package—High Capacity)
Rear	
4x2	Live axle with leaf springs, staggered shock absorbers and stabilizer bar; stabilizer bar standard on DRW models and available with camper package SRW pickups
4x4	Live axle with leaf springs, staggered shock absorbers; stabilizer bar standard on DRW models and available with camper package and camper/snowplow combination package SRW pickups (snowplow package does not come with a rear stabilizer bar)
STEERING	
Type	Power-assist
Overall ratio	20.49:1 (F-250/F-350 4x2); 20.41:1 (F-250/F-350 4x4); 20.41:1 average (F-450)
BRAKES	
Type	Four-wheel vented disc, ABS (standard)
Front	14.29-in. discs
Rear	14.29-in. discs
Assist type	Vacuum (F-250/F-350 SRW)/hydroboost (F-350 DRW/F-450)
WHEELS AND TIRES	
Base wheel and tire	Steel or aluminum; 17-in., 18-in. or 20-in. (F-250/F-350); 17-in. (F-350 DRW); 19.5-in. (F-450)
Largest wheel available	LT275/65R20E All-Terrain OWL (outlined white letter)

2015 FORD F-SERIES SUPER DUTY TECHNICAL SPECIFICATIONS

DIMENSIONS AND CAPACITIES (all dimensions are in inches)										
	Regular		SuperCab				Crew Cab			
	8 ft.		6.75 ft.		8 ft.		6.75 ft.		8 ft.	
	4x2	4x4	4x2	4x4	4x2	4x4	4x2	4x4	4x2	4x4
Wheelbase	137.0	137.0	141.8	141.8	158.0	158.0	156.2	156.2	172.4	172.4
Overall length	227.6	227.6	232.4	232.4	248.6	248.6	246.8	246.8	263.0	263.0
Overall height (F-250)	76.6	79.2	77.0	79.5	76.9	79.3	77.4	79.7	77.3	79.8
Overall height (F-350 SRW)	76.5	80.0	76.9	80.4	76.7	80.2	77.2	80.8	77.2	80.8
Overall height (F-350 DRW)	76.7	79.5	-	-	76.9	79.7	-	-	77.3	79.9
Overall height (F-450 DRW)	-	-	-	-	-	-	-	-	-	79.7
Overall width SRW (excluding mirrors)	79.9	79.9	79.9	79.9	79.9	79.9	79.9	79.9	79.9	79.9
Overall width DRW (excluding mirrors)	96.0	96.0	-	-	96.0	96.0	-	-	96.0	96.0
Overall width with mirrors	104.9	104.9	104.9	104.9	104.9	104.9	104.9	104.9	104.9	104.9
Overall width with mirrors extended	110.0	110.0	110.0	110.0	110.0	110.0	110.0	110.0	110.0	110.0
Cargo box length	98.0	98.0	81.8	81.8	98.0	98.0	81.8	81.8	98.0	98.0
Cargo box width (maximum)	69.3	69.3	69.3	69.3	69.3	69.3	69.3	69.3	69.3	69.3
Width at wheelhouse	50.9	50.9	50.9	50.9	50.9	50.9	50.9	50.9	50.9	50.9
Cargo box height	20.0	20.0	20.0	20.0	20.0	20.0	20.0	20.0	20.0	20.0
Seating capacity	2/3	2/3	5/6	5/6	5/6	5/6	5/6	5/6	5/6	5/6
Headroom										
Front	40.7	40.7	40.7	40.7	40.7	40.7	40.7	40.7	40.7	40.7
Rear	-	-	38.1	38.1	38.1	38.1	40.8	40.8	40.8	40.8
Legroom										
Max Front	43.4	43.3	43.3	43.3	43.3	43.3	43.3	43.3	43.3	43.3
Rear	-	-	31.6	31.6	31.6	31.6	42.1	42.1	42.1	42.1
Hip room										
Front	67.6	67.6	67.6	67.6	67.6	67.6	67.6	67.6	67.6	67.6
Rear	-	-	67.3	67.3	67.3	67.3	67.6	67.6	67.6	67.6
Shoulder room										
Front	68.0	68.0	68.0	68.0	68.0	68.0	68.0	68.0	68.0	68.0
Rear	-	-	68.1	68.1	68.1	68.1	68.0	68.0	68.0	68.0

2015 F-Series Super Duty Payload Capacities

Maximum Payload Package Selector (lbs.)

			Regular Cab	Super Cab		Crew Cab	
		GVWR (lbs)	137.0" WB	141.8" WB	158.0" WB	156.2" WB	172.4" WB
F-250 SRW 4x2		9900	4130	3760	3660	3540	3440
		10000	4240	3860	3760	3640	3540
F-250 SRW 4x4		9900	3630	3350	3250	3150	3040
		10000	3780	3450	3350	3250	3140
F-350 SRW 4x2		10000	4080	3790	3720	3600	3470
		10200	-	-	3920	3800	-
		10500	4540	4250	-	-	3970
		10700	-	3810	-	4260	-
		10800	-	-	3770	3730	-
		10900	-	-	4580	-	-
		11000	4380	4060	-	-	4430
		11100	-	-	-	-	3860
		11400	-	-	4330	4290	4120
		11500	-	-	4430	-	4220
F-350 SRW 4x4		10000	3660	3400	3310	3210	3100
		10400	4060	-	-	-	-
		10500	4110	3900	-	-	-
		10600	-	3950	-	3810	-
		10700	-	-	4010	-	-
		10800	3800	-	4070	3970	3900
		11000	3960	-	4240	-	4060
		11100	4680	4420	-	-	-
		11200	-	3900	3770	3750	4220
		11300	4930	-	3820	4440	3610
		11400	4330	4080	3900	3870	3680
		11500	4430	4170	3990	3970	3780
F-350 DRW 4x2		13000*	6660	-	6150	-	5930
		13500	7260	-	-	-	-
		13900	-	-	7210	-	-
		14000	7060	-	6550	-	7080
F-350 DRW 4x4		13000*	6230	-	5740	-	5520
		13800	7090	-	-	-	-
		14000	6630	-	6890	-	6670
F-450 DRW 4x4		14000	-	-	-	-	5450
Max		-	7260	4420	7210	4440	7080

*Pickup Box Delete

