2020 FORD ESCAPE

TECHNICAL SPECIFICATIONS



Body type	SUV
Construction	Unibody
Trim levels	S, SE, SE Sport, SEL, Titanium
Final assembly location	Louisville Assembly Plant, Louisville, Kentucky

ENGINE

	1.5-liter EcoBoost	2.0-liter EcoBoost	2.5-liter FHEV	2.5-liter PHEV
	S, SE, SEL	SEL, Titanium	SE Sport, Titanium	SE, SEL, Titanium
Configuration	Aluminum block and head, I-3	Aluminum block and head, I-4	Aluminum block and head, Atkinson-cycle I-4	Aluminum block and head, Atkinson-cycle I-4
Manufacturing location	Chihuahua, Mexico	Cleveland and Valencia, Spain	Chihuahua, Mexico	Chihuahua, Mexico
Intake manifold	Composite	Composite	Composite	Composite
Exhaust manifold	Integrated	Integrated	N/A	N/A
Valvetrain	DOHC, Ti-VCT	DOHC, Ti-VCT	DOHC, IVCT	DOHC, IVCT
Pistons	Aluminum	Aluminum	Aluminum	Aluminum
Connecting rods	Powder forged	Powder forged	Powder forged	Powder forged
Bore and stroke	3.31 x 3.54 in.	3.44 x 3.27 in.	3.50 x 3.94 in.	3.50 x 3.94 in.
Displacement	91.4 cu. in.	122 cu. in.	152 cu. in.	152 cu. in.
Compression ratio	10.0:1	9.3:1	13.0:1	13.0:1
Engine control system	Powertrain Control Module	Powertrain Control Module	Powertrain Control Module	Powertrain Control Module
Crankshaft	Forged steel	Forged steel	Forged steel	Forged steel
Horsepower (targeted)	180	250	198	209
Torque (targeted)	177 ftlbs.	275 ftlbs.	N/A	N/A
Recommended fuel	87-octane (minimum)	87-octane (minimum)/ 91+ (rec.)	87-octane (minimum)	87-octane (minimum)
Fuel delivery	GTDI	GTDI	SMFI	SMFI
Fuel capacity	14.7 gallons	15.8 gallons	14.2 gallons	11.0 gallons
Oil capacity (with filter)	5 quarts	5.7 quarts	5.7 quarts	5.7 quarts
Coolant capacity	9 quarts	9.9 quarts	5.5 quarts (gasoline) 11.1 quarts (electric) net	5.5 quarts (gasoline) 11.1 quarts (electric) net
Oil capacity	5 quarts	5.7 quarts	5.7 quarts	5.7 quarts
Coolant capacity	9 quarts	9.9 quarts	5.5 quarts (gasoline) 11.1 quarts (electric) net	5.5 quarts (gasoline) 11.1 quarts (electric) net
DDIVETDAIN				

DRIVETRAIN

Layout	Front-wheel drive and available intelligent all-wheel drive with AWD disconnect	Intelligent all-wheel drive with AWD disconnect	Front-wheel drive and available intelligent all-wheel drive with AWD disconnect	Front-wheel drive

TRANSMISSION

	o-speed automatic with	rowerspill.	rowerspill.
8-speed automatic	SelectShift® with	Electronic continuously	Electronic continuously
	paddle shifters	variable transmission	variable transmission



D	D	Λ	v	ᆮ	c
В	п	А	n	ᆮ	2

Туре	4-wheel disc brakes with ABS	4-wheel disc brakes with ABS	4-wheel disc brakes with ABS and regenerative braking system	4-wheel disc brakes with ABS and regenerative braking system
GEAR RATIOS				
lst	5.34	4.69	N/A	N/A
2nd	3.42	3.31	N/A	N/A
3rd	2.64	3.01	N/A	N/A
4th	2.04	1.92	N/A	N/A
5th	1.42	1.45	N/A	N/A
6th	1	1	N/A	N/A
7th	0.86	0.75	N/A	N/A
8th	0.69	0.62	N/A	N/A
Final gear ratio	3.52:1/3.81:1	N/A/3.47:1	2.91:1/N/A	2.91:1/N/A
Reverse	-4.29	2.96	N/A	N/A

WHEELS AND TIRES

Wheels

17-in. steel with Sparkle Silver-painted covers (standard on S)

17-in. Shadow Silver-painted aluminum (standard on SE; optional on S)

17-in. Ebony-painted aluminum (standard on SE Sport)

19-in. machined-face aluminum with Ebony-painted pockets (included in SE Sport Premium Package; optional on SEL)

18-in. machined-face aluminum with dark stainless-painted pockets (standard on SEL) 19-in. machined-face aluminum with dark tarnished painted pockets (standard on Titanium)

225/65R17 102H all-season (A/S) BSW 2
Tires 225/60R18 all-season (A/S) BSW 225/55R19 all-season (A/S) BSW

DIMENSIONS (INCHES UNLESS OTHERWISE NOTED)

106.7	106.7	106.7	106.7
180.5	180.5	180.5	180.5
74.1	74.1	74.1	74.1
85.6	85.6	85.6	85.6
78.7	78.7	78.7	78.7
66.1	66.1	66.1	66.1
68.6	68.6	68.6	68.6
62.4	62.4	62.4	62.4
61.8	61.8	61.8	61.8
5	5	5	5
5 40	5 40	5 40	5 40
40	40	40	40
40 42.4	40 42.4	40 42.4	40 42.4
40 42.4 57.6	40 42.4 57.6	40 42.4 57.6	40 42.4 57.6
40 42.4 57.6 55.2	40 42.4 57.6 55.2	40 42.4 57.6 55.2	40 42.4 57.6 55.2
40 42.4 57.6 55.2 39.3	40 42.4 57.6 55.2 39.3	40 42.4 57.6 55.2 39.3	40 42.4 57.6 55.2 39.3
40 42.4 57.6 55.2 39.3 40.7	40 42.4 57.6 55.2 39.3 40.7	40 42.4 57.6 55.2 39.3 38.9	40 42.4 57.6 55.2 39.3 38.9
	180.5 74.1 85.6 78.7 66.1 68.6 62.4	180.5 180.5 74.1 74.1 85.6 85.6 78.7 78.7 66.1 66.1 68.6 68.6 62.4 62.4	180.5 180.5 180.5 74.1 74.1 74.1 85.6 85.6 85.6 78.7 78.7 78.7 66.1 66.1 66.1 68.6 68.6 68.6 62.4 62.4 62.4



WFIGH'	TS AND	CAPA	CITIFS

Total passenger volume (cu. ft.)	104	104	104	104
Cargo volume behind first row (cu. ft.)	65.4	65.4	60.8	60.8
Optimized cargo volume, behind second row (cu. ft.)	33.5	33.5	30.7	30.7
Maximum cargo volume, behind second row (cu. ft.)	37.5	37.5	34.4	34.4
Curb weight (FWD/AWD)	3,298 lbs./3,474 lbs.	3,414 lbs./3,566 lbs.	3,554 lbs./3,706 lbs.	3,884 lbs. (FWD only)
ADDITIONAL CARGO DIMENSIO	NS			
Lift-in height	28.1	28.1	28.1	28.1
Cargo height	34.8	34.8	32.8	32.8
Rear opening height	30.4	30.4	30.4	30.4
Maximum cargo height	35.6	35.6	32.8	32.8
Open liftgate height to ground	74.9	74.9	74.9	74.9
Cargo length closed, front row	68.5	68.5	68.3	68.3
Cargo length closed, second row	37.8	37.8	36.7	36.7
Cargo length closed, second row (maximum)	41.8	41.8	40.7	40.7
Cargo length above floor, behind first row	63.2	63.2	63.2	63.2
Cargo length above floor, behind second row	28.8	28.8	28.8	28.8
Cargo length above floor, behind second row (maximum)	32.8	32.8	32.8	32.8
Compartment width (maximum)	57.3	57.3	57.3	57.3
Cargo width, wheelhouse	41.4	41.4	41.4	41.4
Rear opening width, lower	42.1	42.1	42.1	42.1

DRIVER-ASSIST TECHNOLOGY

Ford Co-Pilot360 technologies

Standard

	Auto high-beam headlamps
	Blind Spot Information System with cross-traffic alert
	Lane-Keeping System (includes lane-keeping assist, lane-keeping alert and driver alert)
	Pre-Collision assist with automatic emergency braking (includes pedestrian detection, forward collision warning and dynamic brake support)
	Rearview camera
	Post-collision braking
	Autohold
	Hill Start Assist
Available	
	Active Park Assist 2.0 with reverse and front parking aid
	Adaptive cruise control with stop-and-go
	Evasive steering assist
	Adaptive cruise control with stop-and-go lane-centering

