

2020 FORD F-SERIES SUPER DUTY

TECHNICAL SPECIFICATIONS



BODY

Construction/materials	High-strength fully boxed steel frame, aluminum bed and cab
Body style	Body-on-frame
Trim levels	XL, XLT, Lariat, King Ranch, Platinum, Limited
Final assembly location	Kentucky Truck Plant, Ohio Assembly Plant

DRIVETRAIN

Standard layout	Front-engine, rear-drive
Optional layout	Front-engine, 4x4

ENGINES

	6.2-liter V8	7.3-liter V8	6.7-liter Power Stroke® diesel V8
Configuration	90-degree V8, single overhead cams	90-degree V8, single in-block cams	90-degree diesel V8, single turbocharger, in-block cams and overhead valves
Block/head material	Cast iron block, aluminum heads	Cast iron block, aluminum heads	Compacted graphite iron block, aluminum heads
Displacement	6.2 liters (379 cubic inches)	7.3 liters (445 cubic inches)	6.7 liters (406 cubic inches)
Bore x stroke	4.02 inches x 3.74 inches	4.22 inches x 3.98 inches	3.9 inches x 4.25 inches
Compression ratio	9.8:1	10.5:1	15.8:1
Valvetrain	Two valves per cylinder, roller rocker shaft	Pushrod and rocker arms, two valves per cylinder	Pushrod and rocker arms, four valves per cylinder
Recommended fuel	87 octane	87 octane	Ultra-low sulfur diesel/B20
Fuel delivery	Sequential multi-port electronic	Sequential multi-port electronic	High-pressure common rail
Engine control system	Electronic	Electronic	Electronic
Intake manifold	Naturally aspirated, tuned intake	Naturally aspirated, tuned intake	Single turbocharger, charged air cooler
SAE horsepower	385 @ 5,750 rpm	430 @ 5,500 rpm	475 @ 2,800 rpm
SAE torque	430 lb.-ft. @ 3,800 rpm	475 lb.-ft. @ 4,000 rpm	1,050 lb.-ft. @ 1,600 rpm

FORD F-SERIES SUPER DUTY



ELECTRICAL

Alternator	157-amp standard on XL and XLT with 6.2-liter V8
	200-amp standard on Lariat and above equipped with 6.2-liter V8
	240-amp optional with 6.2-liter V8
	240-amp standard on all models equipped with 7.3-liter V8
	175-amp standard on XL and XLT models equipped with 6.7-liter diesel V8
	240-amp standard on Lariat through Platinum equipped with 6.7-liter diesel V8, optional on XL and XLT
Battery group	175-amp and 157-amp dual alternator standard on Limited, optional on all models equipped with 6.7-liter diesel V8
	240-amp and 157-amp dual alternator optional on all models equipped with 6.7-liter diesel V8
	6.2-liter, 12-volt; 650-CCA/72-amp-hr
	7.3-liter, 12-volt; 750-CCA/78-amp-hr
	6.7-liter, dual 12-volt; 750-CCA/78-amp-hr

STANDARD AND AVAILABLE TECHNOLOGY

AdvanceTrac® with Roll Stability Control® and Trailer Sway Control, Trailer Tire Pressure Monitoring System, Pro Trailer Backup Assist™, Trailer Reverse Guidance, up to seven cameras with four high-definition 180/360-degree cameras, Adaptive Cruise Control, Auto High Beams, Lane-Keeping Alert, Pre-Collision Assist, Blind Spot Information System with Cross-Traffic Alert and trailer tow coverage, FordPass Connect™ with 4G LTE Wi-Fi hotspot for up to 10 devices, SYNC® 3, upfitter interface module (fleet only), BoxLink™ and LED box lighting, remote tailgate release

TRANSMISSIONS

TorqShift® heavy-duty 10-speed automatic with SelectShift®

Configuration	Aluminum 10-speed, available live-drive access on driver side	
Gear ratios	First	4.615:1
	Second	2.919:1
	Third	2.132:1
	Fourth	1.773:1
	Fifth	1.519:1
	Sixth	1.277:1
	Seventh	1:01
	Eighth	0.851:1
	Ninth	0.687:1
	10th	0.632:1
Reverse	-4.695:1	

TorqShift heavy-duty 6-speed automatic with SelectShift (F-250 6.2-liter gas only)

Configuration	Aluminum 6-speed	
Gear ratios	First	4.17:1
	Second	2.34:1
	Third	1.52:1
	Fourth	1.14:1
	Fifth	0.87:1
	Sixth	0.69:1
Reverse	-3.40:1	

FORD F-SERIES SUPER DUTY



SUSPENSION

Front configuration	Independent twin I-beam (narrow front track) with coil springs, shock absorbers, stabilizer bar (F-250 and F-350 4x2) Mono beam (narrow front track) with coil springs, shock absorbers, stabilizer bar (F-250 and F-350 4x4), mono beam (wide front track) with coil springs, shock absorbers, stabilizer bar (F-450)
Front shock absorber type	Heavy-duty gas
Rear configuration	Solid axle, leaf springs
Rear shock absorber type	Heavy-duty gas

STEERING

Type	Power hydraulic
Active features	Adaptive steering and audible lane departure warning available

BRAKES

Type	Four-wheel vented discs with ABS
Front (rotor diameter)	14.29 inches (363 mm), F-250 and F-350 15.39 inches (391 mm), F-450
Rear (rotor diameter)	14.29 inches (363 mm), F-250 and F-350 15.75 inches (400 mm), F-450

FUEL CAPACITY

	Regular Cab	SuperCab	Crew Cab
6.2-liter gas	34 gallons	34 gallons	34 gallons (160-inch wheelbase) 48 gallons (176-inch wheelbase)
7.3-liter gas	34 gallons	34 gallons	34 gallons (160-inch wheelbase) 48 gallons (176-inch wheelbase)
6.7-liter diesel	29 gallons (142-inch wheelbase)	29 gallons (148-inch wheelbase) 34 gallons (164-inch wheelbase)	34 gallons (160-inch wheelbase) 48 gallons (176-inch wheelbase)

WHEELS

Available sizes	17 inches, 18 inches or 20 inches, F-250 and F-350 17 inches DRW, F-350 19.5 inches DRW, F-450
-----------------	--

TIRES

Series	F-250	F-350 SRW	F-350 DRW	F-450
XL	245/75Rx17E BSW A/S	245/75Rx17E BSW A/S	245/75Rx17E BSW A/S	225/70Rx19.5G BSW Traction
XLT	275/65Rx18E BSW A/S	275/65Rx18E BSW A/S	245/75Rx17E BSW A/S	225/70Rx19.5G BSW Traction
Lariat	275/65Rx18E BSW A/S	275/65Rx18E BSW A/S	245/75Rx17E BSW A/S	225/70Rx19.5G BSW Traction
King Ranch	275/65Rx18E BSW A/S	275/65Rx18E BSW A/S	245/75Rx17E BSW A/S	225/70Rx19.5G BSW Traction
Platinum	275/65Rx20E OWL A/T	275/65Rx20E OWL A/T	245/75Rx17E BSW A/S	225/70Rx19.5G BSW Traction
Limited	275/65Rx20E OWL A/T	275/65Rx20E OWL A/T	245/75Rx17E BSW A/S	225/70Rx19.5G BSW Traction
Tremor	35-inch, 285/75R/18E BSW A/T	35-inch, 285/75R/18E BSW A/T	N/A	N/A

FORD F-SERIES SUPER DUTY



EXTERIOR DIMENSIONS

	Regular Cab	SuperCab		Crew Cab	
		SWB	LWB	SWB	LWB
Wheelbase (inches)	141.6	148	164.2	159.8	176
Overall length (inches)	231.8	238.2	254.4	250	266.2
Height, F-250 SRW (without options) (inches)	78.9/81.3	79.3/81.4	78.9/81.4	79.3/81.5	79.0/81.3
Height, F-350 SRW (without options) (inches)	78.7/81.2	79.1/81.3	78.8/81.2	79.1/81.3	78.8/81.1
Height, F-350 DRW (without options) (inches)	79.3/81.3	N/A	79.0/81.3	N/A	79.1/81.5
Height, F-450 DRW (without options) (inches)	82	N/A	N/A	N/A	82.1/82.1
Width, SRW without mirrors (inches)	80	80	80	80	80
Width, DRW/SRW with standard mirrors (inches)	105.9	105.9	105.9	105.9	105.9
Front track, F-250 SRW (inches)	68.3	68.3	68.3	68.3	68.3
Front track, F-350 SRW (inches)	68.3	68.3	68.3	68.3	68.3
Front track, F-350 DRW (inches)	69.1	69.1	69.1	69.1	69.1
Front track, F-450 DRW (inches)	74.8	N/A	N/A	N/A	74.8
Rear track, F-250 SRW (inches)	67.2	67.2	67.2	67.2	67.2
Rear track, F-350 SRW (inches)	67.2	67.2	67.2	67.2	67.2
Rear track, F-350 DRW (inches)	74.7	N/A	74.7	N/A	74.7
Rear track, F-450 DRW (inches)	74.7	N/A	N/A	N/A	74.7
Minimum running ground clearance, F-250 SRW (inches)	8.7/8.5	8.7/8.5	8.7/8.5	8.7/8.5	8.7/8.5
Minimum running ground clearance, F-350 SRW (inches)	8.7/8.5	8.7/8.5	8.7/8.5	8.8/8.5	8.7/8.5
Minimum running ground clearance, F-350 DRW (inches)	8.4/8.3	N/A	8.4/8.3	N/A	8.4/8.3
Minimum running ground clearance, F-450 DRW (inches)	8.6	N/A	N/A	N/A	8.6/8.6
Front overhang (inches)	38.2	38.2	38.2	38.2	38.2
Rear overhang (inches)	52.0	52.0	52.0	52.0	52.0
Angle of departure, F-250 SRW (degrees)	20.2/21.6	19.6/21.1	19.3/21.0	19.3/21.1	18.8/20.8
Angle of departure, F-350 SRW (degrees)	19.2/20.6	18.7/20.3	18.3/20.1	18.2/20.1	17.9/19.8
Angle of departure, F-350 DRW (degrees)	20.3/21.0	N/A	18.6/20.5	N/A	18.3/20.2
Angle of departure, F-450 DRW (degrees)	21.6/21.5	N/A	N/A	N/A	21.1/21.0
Ramp breakover angle, F-250 SRW (degrees)	20.3/24.4	19.3/23.0	17.2/20.9	17.6/21.2	16.0/19.3
Ramp breakover angle, F-350 SRW (degrees)	20.0/24.5	19.0/22.8	17.1/20.7	17.5/20.9	15.9/19.1
Ramp breakover angle, F-350 DRW (degrees)	21.0/24.3	N/A	17.3/20.8	N/A	16.1/19.5
Ramp breakover angle, F-450 DRW (degrees)	25.4/25.4	N/A	N/A	N/A	20.3/20.3
Angle of approach, F-250 SRW (degrees)	17.1/17.2	17.4/17.1	17.6/17.8	17.3/16.9	17.9/17.4
Angle of approach, F-350 SRW (degrees)	16.9/17.1	17.1/16.8	17.7/17.5	17.5/16.7	17.8/17.2
Angle of approach, F-350 DRW (degrees)	17.3/16.9	N/A	17.8/17.4	N/A	18.0/17.9
Angle of approach, F-450 DRW (degrees)	18.5/18.5	N/A	N/A	N/A	18.8/19.0
Open tailgate to ground, F-250 SRW (inches)	36.5/37.6	36.0/37.2	35.7/37.2	35.3/38.1	35.2/36.8
Open tailgate to ground, F-350 SRW (inches)	36.2/37.4	35.8/37.1	35.3/36.9	35.0/38.0	35.0/36.5
Open tailgate to ground, F-350 DRW (inches)	37.3/37.8	N/A	N/A	N/A	35.3/36.9
Open tailgate to ground, F-450 DRW (inches)	38.3/38.1	N/A	N/A	N/A	37.6/37.5

FORD F-SERIES SUPER DUTY



BASE CURB WEIGHTS (LBS.)

	Regular Cab		SuperCab		
	4x2	4x4	SWB 4x2	SWB 4x4	LWB 4x2
F-250 SRW, 6.2-liter	5,677	6,112	5,952	6,376	6,062
F-250 SRW, 6.7-liter	6,483	6,901	6,752	7,154	6,882
F-250 SRW, 7.3-liter	5,782	6,218	6,057	6,482	6,167
F-350 SRW (17-inch wheels), 6.2-liter	5,877	6,305	6,125	6,557	6,238
F-350 SRW (17-inch wheels), 6.7-liter	6,596	7,020	6,823	7,245	6,950
F-350 SRW (17-inch wheels), 7.3-liter	5,911	6,339	6,159	6,591	6,272
F-350 SRW (18-inch wheels A/S), 6.2-liter	5,935	6,362	6,186	6,614	6,295
F-350 SRW (18-inch wheels A/S), 6.7-liter	6,653	7,077	6,880	7,303	7,008
F-350 SRW (18-inch wheels A/S), 7.3-liter	5,969	6,396	6,220	6,648	6,329
F-350 DRW, 6.2-liter	6,144	6,717	N/A	N/A	6,741
F-350 DRW, 6.7-liter	6,896	7,427	N/A	N/A	7,447
F-350 DRW, 7.3-liter	6,276	6,713	N/A	N/A	6,737
F-350 DRW (pickup box delete) (chassis cab), 6.7-liter	6,792	7,191	N/A	N/A	7,149
F-450 DRW, 6.7-liter	7,712	8,012	N/A	N/A	N/A

	SuperCab		Crew Cab		
	LWB 4x4	SWB 4x2	SWB 4x4	LWB 4x2	LWB 4x4
F-250 SRW, 6.2-liter	6,466	6,050	6,462	6,279	6,718
F-250 SRW, 6.7-liter	7,273	6,870	7,262	7,099	7,538
F-250 SRW, 7.3-liter	6,572	6,155	6,568	6,384	6,824
F-350 SRW (17-inch wheels), 6.2-liter	6,666	6,286	6,707	6,513	6,940
F-350 SRW (17-inch wheels), 6.7-liter	7,372	7,004	7,424	7,242	7,675
F-350 SRW (17-inch wheels), 7.3-liter	6,700	6,320	6,741	6,547	6,974
F-350 SRW (18-inch wheels A/S), 6.2-liter	6,723	6,343	6,764	6,570	6,998
F-350 SRW (18-inch wheels A/S), 6.7-liter	7,429	7,061	7,481	7,299	7,732
F-350 SRW (18-inch wheels A/S), 7.3-liter	6,757	6,377	6,798	6,604	7,032
F-350 DRW, 6.2-liter	7,160	N/A	N/A	6,967	7,392
F-350 DRW, 6.7-liter	7,868	N/A	N/A	7,678	8,133
F-350 DRW, 7.3-liter	7,156	N/A	N/A	6,963	7,388
F-350 DRW (pickup box delete) (chassis cab), 6.7-liter	7,544	N/A	N/A	7,301	7,713
F-450 DRW, 6.7-liter	N/A	N/A	N/A	8,282	8,587

INTERIOR DIMENSIONS (INCHES UNLESS OTHERWISE NOTED)

	Regular Cab	SuperCab	Crew Cab
Seating	Three	Six	Six
Front headroom	40.8	40.8	40.8
Front legroom, SAE	43.9	43.9	43.9
Front shoulder room	66.7	66.7	66.7
Front hip room	62.5	62.5	62.5
Rear headroom	N/A	40.3	40.4
Rear legroom, SAE	N/A	33.5	43.6
Rear shoulder room	N/A	65.8	65.9
Rear hip room	N/A	64.7	64.7

FORD F-SERIES SUPER DUTY



CAPACITIES

	Regular Cab		SuperCab		Crew Cab	
	8-foot cargo box	6 ¾-foot cargo box	8-foot cargo box	6 ¾-foot cargo box	8-foot cargo box	
Volume	78.5 cu.-ft.	65.4 cu.-ft.	78.5 cu.-ft.	65.4 cu.-ft.	78.5 cu.-ft.	
Length at floor	98.1 inches	81.9 inches	98.1 inches	81.9 inches	98.1 inches	
Height	21.1 inches	21.1 inches	21.1 inches	21.1 inches	21.1 inches	
Width at floor (maximum)	66.9 inches	66.9 inches	66.9 inches	66.9 inches	66.9 inches	
Width between wheelhouse	50.5 inches	50.5 inches	50.5 inches	50.5 inches	50.5 inches	
Tailgate width	60.5 inches	60.5 inches	60.5 inches	60.5 inches	60.5 inches	
Maximum payload	7,850 lbs.	N/A	N/A	N/A	N/A	
Maximum conventional towing	N/A	N/A	24,200 lbs.	N/A	N/A	
Maximum gooseneck towing	37,000 lbs.	N/A	N/A	N/A	N/A	
Maximum fifth-wheel towing	32,500 lbs.	N/A	32,500 lbs.	N/A	32,500 lbs.	

MAXIMUM PAYLOAD (LBS.)

	GVWR	Regular Cab		SuperCab		Crew Cab	
		Long box	Short box	Long box	Short box	Long box	Short box
F-250 SRW 4x2	9,900	4,160	3,880	3,770	3,780	3,550	
	10,000	4,260	3,980	3,870	3,880	3,650	
	10,600	3,940	N/A	N/A	N/A	N/A	
	10,700	N/A	3,770	N/A	N/A	N/A	
	10,800	N/A	N/A	3,740	3,750	3,520	
F-250 SRW 4x4	9,900	3,720	3,450	3,360	3,370	3,110	
	10,000	3,820	3,550	3,460	3,470	3,210	
	10,800	3,720	3,460	3,310	3,320	3,040	
F-350 SRW 4x2	9,900	3,960	3,710	3,590	3,550	3,320	
	10,000	4,060	3,810	3,690	3,650	3,420	
	10,100	4,160	3,910	N/A	N/A	N/A	
	10,200	N/A	N/A	N/A	3,850	N/A	
	10,400	N/A	N/A	4,090	N/A	N/A	
	10,500	4,500	N/A	N/A	N/A	N/A	
	10,600	3,930	4,350	N/A	N/A	4,020	
	10,700	N/A	3,800	N/A	4,290	N/A	
	10,800	N/A	N/A	N/A	3,720	N/A	
	10,900	N/A	N/A	4,540	N/A	N/A	
	11,000	N/A	N/A	3,980	N/A	N/A	
	11,100	4,380	N/A	N/A	N/A	4,460	
	11,200	N/A	4,250	N/A	N/A	N/A	
	11,300	N/A	N/A	N/A	4,160	N/A	
	11,400	N/A	N/A	4,380	N/A	4,080	
11,500	N/A	N/A	4,420	N/A	4,120		
F-350 SRW 4x4	9,900	3,530	3,270	3,160	3,120	2,890	
	10,000	3,630	3,370	3,260	3,220	2,990	
	10,400	4,030	N/A	N/A	N/A	N/A	
	10,500	N/A	3,870	N/A	N/A	N/A	
	10,600	N/A	N/A	N/A	3,820	N/A	
	10,800	N/A	N/A	4,060	N/A	N/A	
	10,900	4,470	N/A	N/A	N/A	3,890	
11,000	3,910	4,320	N/A	N/A	N/A		

FORD F-SERIES SUPER DUTY



MAXIMUM PAYLOAD (LBS.) CONTINUED

	GVWR	Regular Cab		SuperCab		Crew Cab	
		Long box	Short box	Long box	Short box	Long box	
F-350 SRW 4x4	11,100	N/A	N/A	N/A	4,260	N/A	
	11,200	N/A	N/A	N/A	3,700	N/A	
	11,300	N/A	4,610	4,500	4,460	4,230	
	11,400	4,960	4,080	4,660	3,900	4,390	
	11,500	4,350	4,120	4,700	3,940	4,420	
	11,800	N/A	N/A	4,900	N/A	N/A	
	11,900	N/A	N/A	N/A	N/A	4,730	
	12,000	N/A	N/A	N/A	N/A	4,190	
F-350 DRW 4x2	13,000	6,660	N/A	N/A	N/A	5,960	
	14,000	7,850	N/A	7,190	N/A	6,960	
F-350 DRW 4x4	13,000	6,210	N/A	5,770	N/A	5,530	
	14,000	7,210	N/A	6,770	N/A	6,530	
F-450 DRW 4x2	14,000	6,210	N/A	N/A	N/A	5,630	
F-450 DRW 4x4	14,000	5,900	N/A	N/A	N/A	5,320	
Maximum payload is in F-350 class across all Super Duty models	Overall maximum by cab	7,850, F-350 SRW 2WD 14,000 GCWR	4,610, F-350 SRW 4WD 11,300 GVWR	7,190, F-350 DRW 2WD 14,000 GVWR	4,460, F-350 SRW 4WD 11,300 GVWR	6,960, F-350 DRW 2WD 14,000 GVWR	

MAXIMUM CONVENTIONAL LOADED TRAILER WEIGHT TOW RATINGS (LBS.)

Engine	Rear axle	Axle ratio	Maximum GCWR	Regular Cab						
				F-250 4x2	F-250 4x4	F-350 4x2	F-350 4x4	F-450 4x2	F-450 4x4	
6.2-liter gas V8 (6-speed)	SRW	3.73	19,500	13,300	12,900	13,200	N/A	N/A	N/A	
	SRW	4.3	22,000	14,000	15,000	N/A	N/A	N/A	N/A	
	DRW	4.3	20,000	N/A	N/A	13,300	N/A	N/A	N/A	
6.2-liter gas V8 (10-speed)	SRW	3.73	19,500	N/A	N/A	13,100	12,700	N/A	N/A	
	SRW	4.3	23,000	N/A	N/A	14,000	15,000	N/A	N/A	
	DRW	3.73	20,000	N/A	N/A	13,200	12,800	N/A	N/A	
	DRW	4.3	23,500	N/A	N/A	16,700	16,300	N/A	N/A	
	7.3-liter gas V8	SRW	3.55	21,800	14,000	15,000	N/A	N/A	N/A	N/A
		SRW	3.73	23,500	N/A	N/A	14,000	15,000	N/A	N/A
SRW		4.3	24,900	N/A	N/A	N/A	N/A	N/A	N/A	
SRW		4.3	26,000	14,000	15,000	N/A	N/A	N/A	N/A	
SRW		4.3	27,500	N/A	N/A	14,000	15,000	N/A	N/A	
DRW		3.73	24,000	N/A	N/A	17,200	16,800	N/A	N/A	
DRW		4.3	28,000	N/A	N/A	21,000	20,000	N/A	N/A	
6.7-liter Power Stroke diesel V8	SRW	3.31	23,500	15,000	15,000	N/A	N/A	N/A	N/A	
	SRW	3.31	30,000	15,200	15,000	15,000	15,000	N/A	N/A	
	SRW	3.55	30,000	15,200	15,000	15,000	15,000	N/A	N/A	
	DRW	3.55	40,000	N/A	N/A	21,000	20,000	N/A	N/A	
	DRW	4.1	43,400	N/A	N/A	21,000	20,000	N/A	N/A	
	DRW	4.3	43,500	N/A	N/A	N/A	N/A	21,200	21,200	

FORD F-SERIES SUPER DUTY



MAXIMUM CONVENTIONAL LOADED TRAILER WEIGHT TOW RATINGS (LBS.) CONTINUED

Engine	Rear axle	Axle ratio	Maximum GCWR	SuperCab			
				F-250 4x2	F-250 4x4	F-350 4x2	F-350 4x4
6.2-liter gas V8 (6-speed)	SRW	3.73	19,500	13,000	12,600	N/A	N/A
	SRW	4.3	19,500	N/A	N/A	N/A	N/A
	SRW	4.3	22,000	15,000	15,000	N/A	N/A
	DRW	4.3	20,000	N/A	N/A	N/A	N/A
6.2-liter gas V8 (10-speed)	SRW	3.73	19,500	N/A	N/A	12,800	12,400
	SRW	4.3	23,000	N/A	N/A	15,000	15,000
	DRW	3.73	20,000	N/A	N/A	12,700	12,300
	DRW	4.3	23,500	N/A	N/A	16,200	15,800
7.3-liter gas V8	SRW	3.55	21,800	15,000	14,800	N/A	N/A
	SRW	3.73	23,500	N/A	N/A	15,000	15,000
	SRW	4.3	24,900	N/A	N/A	N/A	N/A
	SRW	4.3	26,000	15,000	15,000	N/A	N/A
	SRW	4.3	27,500	N/A	N/A	15,000	15,000
	DRW	3.73	24,000	N/A	N/A	16,700	16,300
	DRW	4.3	28,000	N/A	N/A	20,700	20,000
6.7-liter Power Stroke diesel V8	SRW	3.31	23,500	15,000	15,000	N/A	N/A
	SRW	3.31	30,000	15,200	20,000	15,000	20,000
	SRW	3.55	30,000	15,200	20,000	15,000	20,000
	DRW	3.55	40,000	N/A	N/A	21,200	21,200
	DRW	4.1	43,400	N/A	N/A	21,200	21,200
	DRW	4.3	43,500	N/A	N/A	N/A	N/A

Engine	Rear axle	Axle ratio	Maximum GCWR	Crew Cab					
				F-250 4x2	F-250 4x4	F-350 4x2	F-350 4x4	F-450 4x2	F-450 4x4
6.2-liter gas V8 (6-speed)	SRW	3.73	19,500	12,900	12,500	N/A	N/A	N/A	N/A
	SRW	4.3	19,500	N/A	N/A	N/A	N/A	N/A	N/A
	SRW	4.3	22,000	15,000	15,000	N/A	N/A	N/A	N/A
	DRW	4.3	20,000	N/A	N/A	N/A	N/A	N/A	N/A
6.2-liter gas V8 (10-speed)	SRW	3.73	19,500	N/A	N/A	12,700	12,300	N/A	N/A
	SRW	4.3	23,000	N/A	N/A	15,000	15,000	N/A	N/A
	DRW	3.73	20,000	N/A	N/A	12,500	12,100	N/A	N/A
	DRW	4.3	23,500	N/A	N/A	16,000	15,600	N/A	N/A
7.3-liter gas V8	SRW	3.55	21,800	15,000	14,700	N/A	N/A	N/A	N/A
	SRW	3.73	23,500	N/A	N/A	15,000	15,000	N/A	N/A
	SRW	4.3	24,900	N/A	15,000	N/A	N/A	N/A	N/A
	SRW	4.3	26,000	15,000	15,000	N/A	N/A	N/A	N/A
	SRW	4.3	27,500	N/A	N/A	15,000	15,000	N/A	N/A
	DRW	3.73	24,000	N/A	N/A	16,500	16,100	N/A	N/A
	DRW	4.3	28,000	N/A	N/A	20,500	20,100	N/A	N/A
6.7-liter Power Stroke diesel V8	SRW	3.31	23,500	15,900	15,400	N/A	N/A	N/A	N/A
	SRW	3.31	30,000	18,200	20,000	18,200	20,000	N/A	N/A
	SRW	3.55	30,000	18,200	20,000	18,200	20,000	N/A	N/A
	DRW	3.55	40,000	N/A	N/A	21,200	21,200	N/A	N/A
	DRW	4.1	43,400	N/A	N/A	21,200	21,200	N/A	N/A
	DRW	4.3	43,500	N/A	N/A	N/A	N/A	24,200	24,200

FORD F-SERIES SUPER DUTY



MAXIMUM FIFTH-WHEEL/GOOSENECK LOADED TRAILER TOW WEIGHT RATINGS (LBS.)*

				Regular Cab					
Engine	Rear axle	Axle ratio	Maximum GCWR	F-250 4x2	F-250 4x4	F-350 4x2	F-350 4x4	F-450 4x2	F-450 4x4
6.2-liter gas V8 (6-speed)	SRW	3.73	19,500	13,300	12,800	13,100	N/A	N/A	N/A
	SRW	4.3	22,000	15,800	15,300	N/A	N/A	N/A	N/A
	DRW	4.3	20,000	N/A	N/A	13,200	N/A	N/A	N/A
6.2-liter gas V8 (10-speed)	SRW	3.73	19,500	N/A	N/A	13,100	12,600	N/A	N/A
	SRW	4.3	23,000	N/A	N/A	16,600	16,100	N/A	N/A
	DRW	3.73	20,000	N/A	N/A	13,200	12,700	N/A	N/A
	DRW	4.3	23,500	N/A	N/A	16,700	16,200	N/A	N/A
7.3-liter gas V8	SRW	3.55	21,800	15,400	15,000	N/A	N/A	N/A	N/A
	SRW	3.73	23,500	N/A	N/A	17,000	16,600	N/A	N/A
	SRW	4.3	24,900	N/A	N/A	N/A	N/A	N/A	N/A
	SRW	4.3	26,000	19,500	19,100	N/A	N/A	N/A	N/A
	SRW	4.3	27,500	19,500	19,100	21,000	20,600	N/A	N/A
	DRW	3.73	24,000	N/A	N/A	17,200	16,700	N/A	N/A
	DRW	4.3	28,000	N/A	N/A	21,200	20,700	N/A	N/A
6.7-liter Power Stroke diesel V8	SRW	3.31	23,500	16,400	16,000	N/A	N/A	N/A	N/A
	SRW	3.31	30,000	22,800	21,800	22,800	22,400	N/A	N/A
	SRW	3.55	30,000	22,800	21,800	22,800	22,400	N/A	N/A
	DRW	3.55	40,000	N/A	N/A	32,400	32,000	N/A	N/A
	DRW	4.1	43,400	N/A	N/A	35,750	35,400	N/A	N/A
	DRW	4.3	43,500	N/A	N/A	N/A	N/A	37,000	36,400

				SuperCab			
Engine	Rear axle	Axle ratio	Maximum GCWR	F-250 4x2	F-250 4x4	F-350 4x2	F-350 4x4
6.2-liter gas V8 (6-speed)	SRW	3.73	19,500	13,000	12,600	N/A	N/A
	SRW	4.3	22,000	15,500	15,100	N/A	N/A
	DRW	4.3	20,000	N/A	N/A	N/A	N/A
6.2-liter gas V8 (10-speed)	SRW	3.73	19,500	N/A	N/A	12,800	12,400
	SRW	4.3	23,000	N/A	N/A	16,300	15,900
	DRW	3.73	20,000	N/A	N/A	12,700	12,300
	DRW	4.3	23,500	N/A	N/A	16,200	15,800
7.3-liter gas V8	SRW	3.55	21,800	15,200	14,700	N/A	N/A
	SRW	3.73	23,500	N/A	N/A	16,800	16,300
	SRW	4.3	24,900	N/A	N/A	N/A	N/A
	SRW	4.3	26,000	19,300	18,800	N/A	N/A
	SRW	4.3	27,500	N/A	N/A	20,800	20,300
	DRW	3.73	24,000	N/A	N/A	16,700	16,300
	DRW	4.3	28,000	N/A	N/A	20,700	20,300
6.7-liter Power Stroke diesel V8	SRW	3.31	23,500	16,200	15,500	N/A	N/A
	SRW	3.31	30,000	22,000	20,100	22,600	22,200
	SRW	3.55	30,000	22,000	20,100	22,600	22,200
	DRW	3.55	40,000	N/A	N/A	32,000	31,600
	DRW	4.1	43,400	N/A	N/A	35,400	35,000
	DRW	4.3	43,500	N/A	N/A	N/A	N/A

FORD F-SERIES SUPER DUTY



MAXIMUM FIFTH-WHEEL/GOOSENECK LOADED TRAILER TOW WEIGHT RATINGS (LBS.)* CONTINUED

Engine	Rear axle	Axle ratio	Maximum GCWR	Crew Cab					
				F-250 4x2	F-250 4x4	F-350 4x2	F-350 4x4	F-450 4x2	F-450 4x4
6.2-liter gas V8 (6-speed)	SRW	3.73	19,500	12,900	12,500	N/A	N/A	N/A	N/A
	SRW	4.3	22,000	15,400	15,000	N/A	N/A	N/A	N/A
	DRW	4.3	20,000	N/A	N/A	N/A	N/A	N/A	N/A
6.2-liter gas V8 (10-speed)	SRW	3.73	19,500	N/A	N/A	12,600	12,200	N/A	N/A
	SRW	4.3	23,000	N/A	N/A	16,100	15,700	N/A	N/A
	DRW	3.73	20,000	N/A	N/A	12,500	12,000	N/A	N/A
7.3-liter gas V8	DRW	4.3	23,500	N/A	N/A	16,000	15,500	N/A	N/A
	SRW	3.55	21,800	15,100	14,700	N/A	N/A	N/A	N/A
	SRW	3.73	23,500	N/A	N/A	16,600	16,200	N/A	N/A
	SRW	4.3	24,900	N/A	17,500	N/A	N/A	N/A	N/A
	SRW	4.3	26,000	19,200	18,600	N/A	N/A	N/A	N/A
	SRW	4.3	27,500	N/A	N/A	20,600	20,200	N/A	N/A
	DRW	3.73	24,000	N/A	N/A	16,500	16,000	N/A	N/A
6.7-liter Power Stroke diesel V8	DRW	4.3	28,000	N/A	N/A	20,500	20,000	N/A	N/A
	SRW	3.31	23,500	16,100	14,700	N/A	N/A	N/A	N/A
	SRW	3.31	30,000	21,700	19,100	22,400	22,000	N/A	N/A
	SRW	3.55	30,000	21,700	19,100	22,400	22,000	N/A	N/A
	DRW	3.55	40,000	N/A	N/A	31,800	31,300	N/A	N/A
	DRW	4.1	43,400	N/A	N/A	35,200	34,700	N/A	N/A
	DRW	4.3	43,500	N/A	N/A	N/A	N/A	34,600	32,600

*Maximum payload and towing numbers are for a base XL model only. Numbers will vary based on trim and options selected. For editorial use only. Information correct at time of publication. Check media.ford.com for updates.

WARRANTY

Bumper-to-bumper	Three years/36,000 miles
Powertrain	Five years/60,000 miles. Diesel, five years/100,000 miles
Corrosion (perforation only)	Five years/unlimited miles
Roadside assistance	Five years/60,000 miles

FORD F-SERIES SUPER DUTY

