2022 FORD EXPEDITION TECHNICAL SPECIFICATIONS (PRELIMINARY)



BODY

BODY		
Construction	Body on frame	
Trimlevels	XL, STX, XLT, Timberline, Limited, King Ranch, Platinum	
Body style	Sport utility vehicle	
Final assembly location	Kentucky Truck Plant, Louisville, Kentucky	
ENGINE		
	Expedition 3.5-liter EcoBoost®	Expedition MAX 3.5-liter EcoBoost
Configuration	60-degree V6	60-degree V6
Manufacturing location	Cleveland Engine Plant	Cleveland Engine Plant
Intake manifold	Nylon 6	Nylon 6
Exhaust manifold	Cast exhaust manifolds	Cast exhaust manifolds
Valvetrain	Twin independent variable camshaft timing (TI-VCT)	Twin independent variable camshaft timing
Pistons	Aluminum alloy	Aluminum alloy
Connecting rods	Forged HS170	Forged HS170
Ignition	Coil-on-plug	Coil-on-plug
Engine block type	Die-cast aluminum	Die-cast aluminum
Cylinder head material	Aluminum alloy	Aluminum alloy
Bore and stroke	3.6 inches x 3.4 inches	3.6 inches x 3.4 inches
Compression ratio	10.0:1	10.0:1
Engine control system	Powertrain control module	Powertrain control module
Crankshaft	Forged steel	Forged steel
Horsepower (XL, XLT, STX)	380 @ 5,000 rpm	380 @ 5,000 rpm
Torque (XL, XLT, STX)	470 lbft. @ 2,250 rpm	470 lbft. @ 2,250 rpm
Horsepower (LIMITED, KR, PLATINUM)	400 @ 5,000 rpm	400 @ 5,000 rpm
Torque (LIMITED, KR, PLATINUM)	480 lbft. @ 2,250 rpm	480 lbft. @ 2,250 rpm
Horsepower (TIMBERLINE, STEALTH)	440 @ 5,000 rpm	440 @ 5,000 rpm
Torque (TIMBERLINE, STEALTH)	510 lbft. @ 2,250 rpm	510 lbft. @ 2,250 rpm
Recommended fuel (minimum)	87 octane	87 octane
Fuel capacity	23.2 gallons	27.8 gallons
Fuel delivery	Gasoline direct injection	Gasoline direct injection
Exhaust	Single, stainless steel	Single, stainless steel
Oil capacity	With oil filter 6.0 quarts	With oil filter 6.0 quarts
EPA-estimated rating	TBD	TBD
DRIVETRAIN		
Lavout	Rear-wheel drive standard; Control Trac® four-wheel drive available	Rear-wheel drive standard; Control Trac® four-wheel drive available

Layout

Rear-wheel drive standard; Control Trac® four-wheel drive available ControlTrac with eLSD (3.73 Limited Slip Differential) – optional on 4x4 trucks

TRANSMISSION

10-speed automatic with SelectShift®

10-speed automatic with SelectShift

optional on 4x4 trucks

ControlTrac with eLSD (3.73 Limited Slip Differential) -




GEAR RATIOS

OLAN NATIOS					
	4x2	4x4	4x2MAX	4x4 MAX	
Final	3.15	3.31	3.31	3.73	
First	4.696				
Second	2.985				
Third	2.146				
Fourth	1.769				
Fifth	1.520				
Sixth	1.275				
Seventh	1.000				
Eighth	0.854				
Ninth	0.689				
10th	0.636				
Reverse	4.866				
SUSPENSION					
Front configuration	Independent sho	ort- and long-arm, coil-ov	er-shocks with stabilizer bar		
Front shocks	Gas-charged (co	Gas-charged (continuously controlled damping available)			
Rear configuration	Independent mu	Independent multi-link with stabilizer bar (mechanical load-leveling available)			
Rearshocks	Gas-charged (co	Gas-charged (continuously controlled damping available)			
STEERING					
Туре	Electric power-a	ssisted rack-and-pinion			
BRAKES					
Туре	Power four-whe	el disc antilock brake syst	em with brake assist and electro	onic brake force distribution	
WHEELS AND TIRES					
Wheels	18-inch ebony-pa 20-inch polished 20-inch six-spok 20-inch luster nic 20-inch dark tarr 22-inch six-spoke 22-inch six-spoke	17-inch steel 18-inch machined-face aluminum with magnetic-painted pockets 18-inch ebony-painted with laser-etched Timberline logo 20-inch polished aluminum 20-inch six-spoke gloss-black painted 20-inch luster nickel-painted aluminum 20-inch dark tarnish-painted 22-inch six-spoke painted machined-face aluminum with dark tarnish-painted pockets and King Ranch center caps 22-inch six-spoke painted machined-face aluminum with dark tarnish-painted pockets 22-inch premium black-painted aluminum			
Tires	275/55R20, Limi 285/45R22, King 285/45R22, Plati	275/65R18, STX/XLT 275/55R20, Limited 285/45R22, King Ranch 285/45R22, Platinum P265/70R18E All-Terrain, Timberline			

DIMENSIONS (INCHES UNLESS OTHERWISE NOTED)

EXTERIOR		
Wheelbase	122.5	131.6
Length	210	221.9
Width, excluding mirrors	79.9	79.9
Width, including mirrors	93.4	93.4
Width, mirrors folded	83.6	83.6
Vehicle height	76.6, 4x2; 76.4, 4x4	76.4, 4x2; 76.2, 4x4
Track, front, rear	67.6, 67.2	67.6, 67.2
Front overhang	38.2	38.2
Rear overhang	49.3	49.3





Approach angle, 4x2	23.4 degrees		24 degrees		
Approach angle, 4x4	23.3 degrees /28.5 degrees (Timberline)		23.7 degrees		
Departure angle, 4x2	22.2 degrees	degrees		21.5 degrees	
Departure angle, 4x4	ure angle, 4x4 21.9 degrees /23.7 degrees (Timb		21.3 degrees		
Ramp breakover angle, 4x2	21.5 degrees		20.3 degrees		
Ramp breakover angle, 4x4	21.4 degrees /21.9 degree	s (Timberline)	20.1 degrees		
Minimum running ground clearance	inimum running ground clearance 9.8 / 10.6 (Timberline)		9.8, 4x2; 9.7, 4x4		
INTERIOR					
Seating capacity	Eight; Five on STX		Eight		
First-row headroom	42.0		42.0		
First-row legroom (maximum)	42.0		43.9		
First-row shoulder room	43.9 64.9		64.9		
First-row hip room	64.9 62.2		62.2		
Second-row headroom	62.2 40.0		40.0		
Second-row legroom	40.0 41.5		41.5		
Second-row legroom (maximum)	41.5		42.6		
Second-row shoulder room	42.6 64.8		64.8		
Second-row hip room	64.8 62.6		62.6		
Third-row headroom	37.3		37.4		
Third-row headroom 37.3 Third-row legroom 36.1			36.1		
Third-row legroom (maximum)	40.9		40.9		
Third-row shoulder room	64.2		64.3		
Third-row bip room	51.4		51.4		
	5		5		
WEIGHTS AND CAPACITIES					
Total passenger volume	171.9 cu. ft.		172.0 cu. ft.		
Cargo volume behind first row	104.6 cu. ft.		121.5 cu. ft.		
Cargo volume behind second row	57.5 cu. ft.		73.3 cu. ft.		
Cargo volume behind second row (maximum)	63.6 cu. ft.		79.6 cu. ft.		
Cargo volume behind third row	19.3 cu. ft.		34.3 cu. ft.		
Cargo volume behind third row (maximum)	20.9 cu. ft.		36.0 cu. ft.		
Base curb weight, 4x2	5,306 lbs.		5,434 lbs.		
Base curb weight, 4x4	5,532 lbs.		5,668 lbs.		
TOWING					
	4x2	4x4	4x2 MAX	4x4 MAX	
Maximum trailer weight	4x2 6,600 lbs.	4x4 6,500 lbs.	6,600 lbs.	6,600 lbs.	
Maximum trailer weight	0,000 lbs.	0,500 lbs.	0,000 lbs.	0,000 lbs.	
Maximum trailer weight with available Heavy-Duty Trailer Towing Package	9,300 lbs.	9,200 lbs.	9,000 lbs.	9,000 lbs.	
GCWR	12,300 lbs.	12,500 lbs.	12,500 lbs.	12,800 lbs.	
GCWR with available Heavy-Duty Trailer Towing Package	14,900 lbs.	15,200 lbs.	15,100 lbs.	15,300 lbs.	
TECHNOLOGY					
	Adaptivo cruiso control w	ith ston-and-go			
DRIVER-ASSIST STANDARD FEATURES	Adaptive cruise control with stop-and-go Pre-Collision Assist with Automatic Emergency Braking and Forward Collision Warning Lane-Keeping System Enhanced active park assist Active Air Dam Cross-traffic alert				
DRIVER-ASSIST OPTIONAL FEATURES	Evasive Steering Assist Ford BlueCruise Intersection Assist Reverse Brake Assist Road Edge Detection				

For editorial use only. Information correct at time of publication. Check media.ford.com for updates.

