# 2023 FORD F-150® RAPTOR™ LINEUP

# TECHNICAL SPECIFICATIONS



Preproduction 2023 F-150 Raptor R shown. Available late 2022.

|              |                     |   | • |
|--------------|---------------------|---|---|
| О            | $\boldsymbol{\cap}$ | п | V |
| $\mathbf{n}$ | u                   |   | т |

| Construction/materials  | High-strength steel frame, aluminum cabin and bed |
|-------------------------|---|
| Body configuration      | SuperCrew®  |
| Final assembly location | Dearborn Truck Plant                              |

#### **DRIVETRAIN**

Layout Longitudinally mounted front-engine 10-speed automatic transmission, 2-speed torque on-demand 4x4 with mechanical lock; electronic locking rear differential with 4.10 axle

#### **ENGINE**

| Raptor                |   | Raptor R   |  |
|-----------------------|---|--|--|
| Configuration         | High-output 3.5-liter twin-turbocharged, intercooled 60-degree overhead-cam EcoBoost V6 | High-output 5.2-liter supercharged, intercooled 90-degree overhead-cam V8  |  |
| Block/head material   | Aluminum block, aluminum heads  | Cast aluminum block and head with plasma transfer wire arc cylinder liners |  |
| Displacement          | 3.5 liters (213 cubic inches)   | 5.2 liters (315 cubic inches)  |  |
| Bore x stroke         | 3.64 in. x 3.41 in.   | 3.70 in. x 3.66 in.  |  |
| Compression ratio     | 10.5:1  | 9.5:1  |  |
| Valvetrain            | DOHC, four valves per cylinder, twin independent variable camshaft timing               | DOHC, four valves per cylinder, twin independent variable camshaft timing  |  |
| Pistons material      | Aluminum alloy  | Forged aluminum  |  |
| Ignition system       | Distributor-less with coil-on-plug  | Distributor-less with coil-on-plug   |  |
| Recommended fuel      | Premium unleaded  | Premium unleaded   |  |
| Fuel delivery         | Port fuel injection with direct injection   | Port fuel injection with twin high-flow fuel pumps                         |  |
| Engine control system | Electronic  | Ford powertrain control module   |  |
| Oil capacity          | 6 quarts  | 11.5 quarts 5W-50 full synthetic with filter                               |  |
| Coolant capacity      | 13.0 liters   | 12.0 liters (engine), 3.1 liters (supercharger)                            |  |
| SAE horsepower*       | 450 @ 5,850 rpm   | 700 @ 6,650 rpm  |  |
| SAE torque*           | 510 lbft. @ 3,000 rpm   | 640 lbft. @ 4,250 rpm  |  |
| Build location        | Cleveland, Ohio   | Dearborn, Michigan   |  |

# **ELECTRICAL**

| Alternator         | Standard single 240A | Standard single 240A |
|--------------------|----------------------|----------------------|
| Battery group, CCA | H7 AGM 80AH 800CCA   | H7 AGM 80AH 800CCA   |

#### TRANSFER CASE

| Type               | Hi-lock transfer case; two-speed automatic four-<br>wheel-drive system with neutral towing capability | Hi-lock transfer case; two-speed automatic four-<br>wheel-drive system with neutral towing capability |
|--------------------|---|---|
| 4-high drive ratio | 1:1   | 1:1   |
| 4-low drive ratio  | 2.64:1  | 2.64:1  |





# **FINAL DRIVE**

|   | Raptor | Raptor R |
|---|--------|----------|
| Final drive front/rear axle ratios      | 4.10:1 | 4.10:1   |
| Final drive front axle ratio (optional) | 4.10:1 | 4.10:1   |

# **TRANSMISSION**

|               | 10-speed SelectShift® Automatic                        |   |  |
|---------------|--|---|--|
| Configuration | Electronically controlled hydraulic 10-speed automatic |   |  |
|               | First  | 4.69                                      |  |
|               | Second   | 2.98                                      |  |
|               | Third  | 2.14                                      |  |
|               | Fourth   | 1.76                                      |  |
| Gearratios    | Fifth  | 1.52                                      |  |
|               | Sixth  | 1.27                                      |  |
|               | Seventh  | 1   |  |
|               | Eighth   | 0.85                                      |  |
|               | Ninth  | 0.69                                      |  |
|               | 10th   | 0.63                                      |  |
|               | Reverse  | 4.86                                      |  |
|               | Cooling  | Warm up unit with thermostatic fin cooler |  |

#### **SUSPENSION**

| Front configuration                | Independent  double-wishbone with  coil-over shock and cast a luminum lower  control arm and control arm |
|------------------------------------|--|
| Front shock absorber type/diameter | High-output, gas-pressurized, electronically controlled continuously variable compression damping FOX Racing Shox $^{\!\!\!\!\wedge}$ , 3.1-inch damper, 0.875-inch rod diameter (standard), 1.0-inch rod diameter with optional 37-inch tires (standard with Raptor R)  |
| Rearconfiguration                  | Five-link coil with Panhard rod  |
| Front travel                       | 14.0-inch (standard), 13.0-inch with optional 37-inch tires (standard with Raptor R)   |
| Rear shock absorber type/diameter  | High-output, gas-pressurized, electronically controlled continuously variable compression damping FOX Racing Shox™, 3.1-inch damper, 0.875-inch rod diameter   |
| Rear travel                        | 15.0-inch (standard), 14.1-inch with optional 37-inch tires (standard with Raptor R)   |
|                                    |  |

# **STEERING**

|                               | Raptor  | Raptor R                |
|-------------------------------|---|-------------------------|
| Туре                          | Electric power-assisted                           | Electric power-assisted |
| Ratio                         | 17.2:1  | 17.2:1                  |
| Turning circle (curb to curb) | 35-in. tires – 48.0 ft.<br>37-in. tires – 50.0 ft | 37-in. tires – 50.0 ft. |

# **BRAKES**

| Front type                              | Power antilock vented disc            | Power anti-lock vented disc           |
|---|---------------------------------------|---------------------------------------|
| Booster type                            | Electronically controlled brake boost | Electronically controlled brake boost |
| Front rotor diameter/thickness/material | 350 x 34 mm Nitro Tough iron          | 350 x 34 mm Nitro Tough iron          |
| Front caliper configuration             | 2 x 51 mm sliding caliper             | 2 x 51 mm sliding caliper             |
| Front pad material                      | FER9213                               | FER9213                               |
| Front swept area                        | 51,547 mm <sup>2</sup>                | 51,547 mm <sup>2</sup>                |
| Reartype                                | Power antilock vented disc            | Power antilock vented disc            |
| Rear rotor diameter/thickness/material  | 336 x 20 mm Nitro Tough iron          | 336 x 20 mm Nitro Tough iron          |
| Rear caliper configuration              | 1 x 54 mm sliding eiPB                | 1 x 54 mm sliding eiPB                |
| Rear pad material                       | GA9105                                | GA9105                                |
| Rear swept area                         | 40,998 mm <sup>2</sup>                | 40,998 mm <sup>2</sup>                |
| Parking/emergency brake                 | 25.5 kN electronic parking brake      | 25.5 kN electronic parking brake      |



#### **FUEL CAPACITY**

| SuperCrew | 36 gallons (Raptor and Raptor R) |
|-----------|----------------------------------|
|           |                                  |

#### **FUEL ECONOMY**

|  | EPA-estimated fuel economy rating |         |          |
|--|-----------------------------------|---------|----------|
|  | City                              | Highway | Combined |
| 2022 Raptor                                      | 15 mpg                            | 18 mpg  | 16 mpg   |
| 2022 Raptor without Start/Stop                   | 14 mpg                            | 18 mpg  | 15 mpg   |
| 2022 Raptor with 37-in. tires                    | 15 mpg                            | 16 mpg  | 15 mpg   |
| 2022 Raptor with 37-in. tires without Start/Stop | 14 mpg                            | 16 mpg  | 15 mpg   |
| 2023 Raptor R without Start/Stop                 | TBD                               | TBD     | TBD      |

# **SAFETY/CONTROL SYSTEMS**

|                       | Raptor   | Raptor R   |
|-----------------------|--|--|
| ABS/stability control | Four-wheel antilock brakes, AdvanceTrac with Roll Stability Control  | Four-Wheel Anti-Lock Brakes, AdvanceTrac® with Roll Stability Control™ (RSC®)  |
| Airbags               | Front, driver and passenger<br>Front, driver and passenger seat-mounted side<br>Safety Canopy® side curtains<br>Front, driver and passenger knee | Front, driver and passenger<br>Front, driver and passenger seat-mounted side<br>Safety Canopy® side curtains<br>Front, driver and passenger knee |
| Chassis safety        | Tire Pressure Monitoring System (TPMS),<br>SOS Post-Crash Alert System™  | Tire Pressure Monitoring System (TPMS),<br>SOS Post-Crash Alert System™  |

# **WHEELS AND TIRES**

| Standard                  | 17 x 8.5-inch cast aluminum wheels with bright machined face and Magnetic painted pockets, LT315/70R17 BFGoodrich® All-Terrain T/A® KO2 Tires   | wheels, Matte Black 10 painted wheel with  Magnetic painted ring, available Code Orange ring, L37x12.50R17LT BFGoodrich All-Terrain T/A KO2 Tires |
|---------------------------|---|---|
| Available                 | 17 x 8.5-inch unique pattern forged aluminum<br>beadlock-capable wheels, Magnetic painted wheel<br>and ring, 37x12.50R17LT BFGoodrich All-Terrain T/A<br>KO2 Tires Load Range"C"-116S |   |
| Spare (Under-bed mounted) | Full-size matching spare wheel and tire   | Full-size matching spare wheel and tire   |

# **LIGHTING**

| Headlamps | leveling, dynamic bending and daytime running lamp  |
|-----------|---|
| Taillamps | LED   |
| Auxiliary | Daytime running lamp, cargo lamp, integrated marker lights, tailgate LED, LED side-mirror spotlights, LED cargo box lights, Rigid™ LED fog lamps and off-road driving lamp package (optional) |

#### **EXTERIOR DIMENSIONS**

|                         | SuperCrew with 35-inch tires | SuperCrew with 37-inch tires/Raptor R |
|-------------------------|------------------------------|---------------------------------------|
| Wheelbase               | 145.4                        | 145.4                                 |
| Overall length          | 232.6                        | 232.6                                 |
| Overall width           | 96.0                         | 96.0                                  |
| Width w/o mirrors       | 86.6                         | 87.0                                  |
| Overall height          | 79.8                         | 80.6                                  |
| Track width, front      | 74.0                         | 74.3                                  |
| Track width, rear       | 73.6                         | 73.9                                  |
| Ground clearance        | 12.0                         | 13.1                                  |
| Approach angle          | 31.0 degrees                 | 33.1 degrees                          |
| Departure angle         | 23.9 degrees                 | 24.9 degrees                          |
| Breakover angle         | 22.7 degrees                 | 24.4 degrees                          |
| Open tailgate to ground | 37.0                         | 37.8                                  |
|                         |                              |                                       |



 $Standard\,LED\,quad-beam\,with\,day time\,running\,lamp\,or\,optional\,adaptive\,LED\,projector\,with\,automatic$ 

# INTERIOR DIMENSIONS (INCHES UNLESS OTHERWISE NOTED)

|                       | Raptor | Raptor R |
|-----------------------|--------|----------|
| Seating               | Five   | Five     |
| Front headroom        | 40.8   | 40.8     |
| Maximum front legroom | 43.9   | 43.9     |
| Front shoulder room   | 66.6   | 66.6     |
| Front hip room        | 62.5   | 62.5     |
| Rear headroom         | 40.4   | 40.4     |
| Maximum rear legroom  | 43.6   | 43.6     |
| Rear shoulder room    | 65.8   | 65.8     |
| Rear hip room         | 62.6   | 62.6     |

#### **CAPACITIES (INCHES UNLESS OTHERWISE NOTED)**

| Length at floor             | 67.1         | 67.1         |
|-----------------------------|--------------|--------------|
| Width at wheelhouse         | 50.6         | 50.6         |
| Maximum width inside box    | 65.2         | 65.2         |
| Rear opening width          | 60.3         | 60.3         |
| Cargo volume                | 52.8 cu. ft. | 52.8 cu. ft. |
| Maximum payload             | 1,400 lbs.   | 1,400 lbs.   |
| Maximum conventional towing | 8,200 lbs.   | 8,700 lbs.   |

#### **TECHNOLOGY**

Ford PowerUp over-the-air-updates, FordPass® Connect (with remote lock/unlock, vehicle status check, schedule remote start times, Trailer Theft Alert, Trailer Light Check and other truck features), 12-inch digital productivity screen, 12-inch touch screen, SYNC® 4, Intelligent Access with push-button start, SecuriCode™ keyless entry keypad, Remote Start System, SiriusXN

screen, SYNC® 4, Intelligent Access with push-button start, SecuriCode™ keyless entry keypad, Remote Start System, SiriusXM® with 360L, 4G LTE with Wi-Fi® hotspot, MyKey®, Onboard 400W outlet, MyMode™, pre-wired overhead auxiliary switches with under-hood distribution box, Reverse Sensing System and Adaptive Cruise Control

Off-road Terrain Management System™, Trail Control™, Trail 1 Pedal Drive, Trail Turn Assist

Available

2.0-kilowatt Pro Power Onboard (Raptor only), connected built-in navigation, 360-degree camera with split-view display, 18speaker B&O sound system Unleashed by Bang & Olufsen with HD Radio™ and rain-sensing wipers, Pro Trailer Hitch Assist

#### FORD CO-PILOT360™ TECHNOLOGIES

Auto Hold, auto on/off headlamps, auto high-beam headlamps, Forward Collision Warning and Dynamic Brake Support,
Standard Hill Start Assist, Pre-Collision Assist with Automatic Emergency Braking (with Pedestrian Detection), rearview camera with
Dynamic Hitch Support, Blind Spot Information System with Cross-Traffic Alert, Trailer Coverage and Reverse Brake Assist

Available Active Drive Assist Prep Kit, Distance Alert/Distance Indication, Forward Sensing System, Pro Trailer Backup Assist and Trailer Reverse Guidance

#### **WARRANTY**

| Bumper-to-bumper  | Three years/36,000 miles   | Three years/36,000 miles   |
|---|----------------------------|----------------------------|
| Powertrain  | Five years/60,000 miles    | Five years/60,000 miles    |
| Aluminum body panels  | Five years/unlimited miles | Five years/unlimited miles |
| Corrosion, sheetmetal (perforation only excluding aluminum) | Five years/unlimited miles | Five years/unlimited miles |
| Paint adhesion  | Five years/unlimited miles | Five years/unlimited miles |
| Roadside assistance   | Five years/60,000 miles    | Five years/60,000 miles    |

