2016 FORD MUSTANG TECHNICAL SPECIFICATIONS

BODY								
Construction	Construction Unitized welded steel body, aluminum hood and front fenders							
Body styles		Fastback and convertible						
Final assembly location Flat Rock, Michigan								
ENGINE		1						
		3.7-liter V6		2.3-liter EcoBoost® I	-4	5.0-liter V8		
Configuration		Aluminum block and I		Aluminum block and head		Aluminum block and heads		
Intake manifold		Composite shell-welded with runner pack		Composite shell-welded with runner pack		Composite shell-welded with runner pack and charge motion control valves		
Exhaust manifold		Cast iron		Three-port integrated into aluminum head		Stainless steel tubular headers		
Valvetrain		DOHC, four valves per cylinder, twin independent variable camshaft timing		DOHC, four valves per cylinder, twin independent variable camshaft timing		DOHC, four valves per cylinder, twin independent variable camshaft timing		
Valve diameter/lift		Intake, 37 mm/10 mm; exhaust, 31 mm/9.7 mm		Intake, 31 mm/8.31 mm; exhaust, 30 mm/7.42 mm		Intake, 37.3 mm/13 mm; exhaust, 31.8 mm/13 mm		
Pistons		Cast aluminum		Cast aluminum		Cast aluminum		
Connecting rod	ls	Forged steel		Forged steel		Forged steel		
Ignition		Distributor-less with coil-on-plug		Distributor-less with coil-on-plug		Distributor-less with coil-on-plug		
Bore x stroke		3.76 x 3.41 in. (95.5 x 86.7 mm)		3.45 x 3.7 in. (87.55 x 94 mm)		3.63 x 3.65 in. (92.2 x 92.7 mm)		
Displacement		227 cu. in. (3,727 cc)		140 cu. in. (2,300 cc)		302 cu. in. (4,951 cc)		
Compression ratio		10.5:1		9.5:1		11.0:1		
Engine control system		PCM		PCM		PCM		
Horsepower		300 @ 6,500 rpm		310 @ 5,500 rpm		435 @ 6,500 rpm		
Torque		280 lbft. @ 4,000 rpm		320 lbft. @ 2,500 rpm to 4,500 rpm		400 lbft. @ 4,250 rpm		
Recommended fuel		87-octane		87-octane		87-octane, minimum		
Fuel capacity		16 gallons		15.5 gallons		16 gallons		
Fuel delivery		Sequential multiport electronic		Direct injection		Sequential multiport electronic		
Oil capacity		Six quarts 5W-20 with filter (10,000-mile service interval)		Six quarts 5W-30 with filter (10,000-mile service interval)		Eight quarts 5W-20 with filter (10,000-mile service interval)		
EPA-estimated fuel economy ratings		19 mpg city, 28 mpg highway, 22 mpg combined, automatic; 17 mpg city, 28 mpg highway, 21 mpg combined, manual		21 mpg city, 32 mpg highway, 25 mpg combined, automatic; 22 mpg city, 31 mpg highway, 25 mpg combined, manual		16 mpg city, 25 mpg highway, 19 mpg combined, automatic; 15 mpg city, 25 mpg highway, 19 mpg combined, manual		
Layout	Rear-whe	el drive with limited-sli	p differ	ential				
TRANSMISSI	ON							
	3.7-liter V6		2.3-liter EcoBoost I-4 5.		0-liter V8			
Standard	Six-speed	manual with hill start	assist					
Gear ratios								
1st 4.236:1			4.236	:1 3.0		657:1		

2016 FORD MUSTANG TECHNICAL SPECIFICATIONS

2nd	2.538:1		2.538:1	2.430:1						
3rd	1.665:1		1.665:1	1.686:1						
4th	1.2387:1		1.238:1	1.315:1						
5th	1.00:1		1.00:1	1.00:1						
6th	0.704:1		0.704:1	0.651:1						
Final drive	3.15:1, 3.55	5:1 (optional)	3.31:1, 3.55:1 (Performance Package)	3.31:1, 3.55:1 (optional), 3.73:1 Torsen (Performance Package)						
Optional	Optional Six-speed automatic with paddle shifters									
Gear ratio	s									
1st	4.17:1	4.17:1								
2nd	2.34:1	2.34:1								
3rd	1.52:1	1.52:1								
4th	1.14:1	1.14:1								
5th	0.87:1	0.87:1								
6th	0.69:1	0.69:1								
Final drive	3.15:1, 3.55	5:1 (optional)	3.15:1, 3.31:1 (optional), 3.55:1 (Performance Package)							
SUSPENSI	ON									
Front		Double-ball-joint i	ndependent MacPherson strut and tubular stabilizer bar							
			pendent with coil springs, solid stabilizer bar and twin- or mono- plication-specific)							
STEERING	1									
Туре		Electric power-ass	sisted, rack-and-pinion							
Ratio		16:1								
Turning circ curb-to-cur	•	36.5 ft. (17-in. wheels), 37.8 ft. (18-in. and 19-in. wheels), 40.0 ft. (Performance Package and 20-in. wheels)								
BRAKES										
Туре	3.7-liter V6		2.3-liter EcoBoost I-4	5.0-liter V8						
	Four-wheel po	electronic	2.3-liter EcoBoost I-4 Four-wheel power disc brakes with four-sensor, four-channel antilock braking system and AdvanceTrac electronic stability control	5.0-liter V8 Four-wheel power disc brakes with four-sensor, four-channel antilock braking system and AdvanceTrac electronic stability control						
Front	Four-wheel po with four-sens antilock brakin AdvanceTrac®	or, four-channel og system and electronic ol vented discs, -mm floating	Four-wheel power disc brakes with four-sensor, four-channel antilock braking system and AdvanceTrac electronic stability	Four-wheel power disc brakes with four-sensor, four-channel antilock braking system and AdvanceTrac electronic stability						
	Four-wheel po with four-sens antilock brakin AdvanceTrac® stability contro 320 x 30-mm twin-piston 43 aluminum calip	or, four-channel or system and electronic ol vented discs, -mm floating pers solid discs, es-mm floating pers,	Four-wheel power disc brakes with four-sensor, four-channel antilock braking system and AdvanceTrac electronic stability control 320 x 30-mm vented discs, twin-piston 43-mm floating aluminum calipers; 352 x 32-mm vented discs, four-piston 46-mm fixed aluminum calipers	Four-wheel power disc brakes with four-sensor, four-channel antilock braking system and AdvanceTrac electronic stability control 352 x 32-mm vented discs, four-piston 46-mm fixed aluminum calipers; 380 x 34-mm vented discs, Brembo six-piston 36-mm fixed aluminum						
Front	Four-wheel po with four-sens antilock brakin AdvanceTrac® stability control 320 x 30-mm twin-piston 43 aluminum calip 320 x 12-mm single-piston 4 aluminum calip	or, four-channel or system and electronic ol vented discs, -mm floating pers solid discs, 15-mm floating pers, 1g brake	Four-wheel power disc brakes with four-sensor, four-channel antilock braking system and AdvanceTrac electronic stability control 320 x 30-mm vented discs, twin-piston 43-mm floating aluminum calipers; 352 x 32-mm vented discs, four-piston 46-mm fixed aluminum calipers (Performance Package) 320 x 12-mm solid discs, single-piston 45-mm floating aluminum calipers, integral parking brake; 330 x 25-mm vented discs, single-piston 45-mm floating iron calipers, integral parking brake	Four-wheel power disc brakes with four-sensor, four-channel antilock braking system and AdvanceTrac electronic stability control 352 x 32-mm vented discs, four-piston 46-mm fixed aluminum calipers; 380 x 34-mm vented discs, Brembo six-piston 36-mm fixed aluminum calipers (Performance Package) 330 x 25-mm vented discs, single-piston 45-mm floating iron calipers, integral parking brake; 330 x 25-mm vented discs, single-piston 45-mm floating iron calipers, integral parking brake						

2016 FORD MUSTANG TECHNICAL SPECIFICATIONS

Optional	18 x 8-in. 235/50RW A/S		19 x 8.5-in. 255/40RW A/S, 20 x 9-in. 265/35RW summer, 19 x 9-in. 255/40RY summer (Performance Package)		ımmer,	19 x 8.5-in. 255/40RW A/S, 20 x 9-in. 265/35RW summer front; 19 x 9-in. 255/40R, rear, 19 x 9.5-in. 275/40RY summer (Performance Package)	
DIMENSI	ONS (inches un	less otherwise no	oted)				
		Fastback			Convertible		
EXTERIOR	2						
Wheelbase		107.1		107.1			
Overall length		188.3		188.3			
Overall wid	lth	75.4		75.4			
Overall height		54.4		54.9			
Track, front, rear		62.3, 64.9		62.3, 64.9			
INTERIOR	ł						
Seating capacity		Four			Four		
Front headroom		37.6			37.6		
Front legroom, maximum		44.5			44.5		
Front shou	lder room	56.3			56.3		
Front hip room		54.9			54.9		
Rear headroom		34.8		35.7			
Rear legroom		30.6		30.8			
Rear shoulder room		52.2		44.7			
Rear hip room		47.4		43.7			
BASE CUR	B WEIGHT						
3.7-liter V		3.7-liter V6	2.3-liter Eco		Boost I-	4 5.0-liter V8	
Fastback, manual		3,526 lbs.		3,532 lbs.		3,705 lbs.	
Fastback, automatic		3,530 lbs. 3,524 lbs.		3,524 lbs.		3,729 lbs.	
CAPACITI	ES						
Passenger volume		84.5 cu. ft.		80.8 cu. ft.			
		T					

For editorial use only. Information correct at time of publication. Check <u>media.ford.com</u> for updates.

11.4 cu. ft.

13.5 cu. ft.

Cargo volume